



Swd Rheinol Primol Power Synth. CS

SAE 5W-30

Fully Synthetic High Performance Low Friction Oil for Passenger Car Engines

Properties

Swd Rheinol Primol Power Synt CS SAE 5W30 is a fully synthetic low friction oil for all passenger car gasoline- and diesel-engines. It is exclusively made from high quality synthese baseoil, which are combined with additives of the most progressive technology.

Swd Rheinol Primol Power Synt CS SAE 5W30 provides reduced oil- and fuel-consumption because of its optimized formulation. Excellent dispersancy prevents deposits und pluggings in the oil circuit and thus keeps the motor clean. Outstanding low-temperature properties enable smooth cold start and quick oiling of the engine, even at frost. Modern oxidation inhibitors and the fully synthetic base increase the service life of the oil and the assured wear protection are best conditions for a long motor life.

Swd Rheinol Primol Power Synt CS SAE 5W30 is outstandingly applicable at all operation conditions (highway, city traffic, s.a.o.) in modern passenger car engines, wether turbo charged or not.

Specifications

ACEA A3-/B4-08
API SN / CF

Typical Values

Swd Rheinol Primol Power Synth. CS SAE 5W-30	unit	value	method
Density at 15°C	kg/m ³	855	DIN 51 757
Viscosity at 40°C	mm ² /s	61,7	DIN 51 562
Viscosity at 100°C	mm ² /s	10,6	DIN 51 562
Viscosity Index		163	DIN ISO 2909
CCS at -30°C	mPa.s	5230	DIN 51 377
Pourpoint	°C	-42	DIN ISO 3016
Flashpoint	°C	230	DIN ISO 2592
TBN	mg KOH/g	8,2	DIN ISO 3771

Article-Number : **31371**

Specification variations in these characteristics may occur.
The instructions of manufacturer must be regarded.
Further informations to be available by MSDS.

Swd Lubricants GmbH & Co. KG
Am Schlütershof 26
D-47059 Duisburg
Tel.: 0203 / 3191940
Fax: 0203 / 3191998